

MULTI SPLIT

Multi Combination Table for 2 & 3 Rooms–Cooling/Heating

2 Rooms Multi cooling

AOYG14LAC2	Combination of Indoor Unit		COOLING OPERATION					EER	Seasonal Data		
			Cooling Capacity			Input Power (min-max)	Pdesign		SEER	Energy efficiency class	
			Room 1	Room 2	Total Capacity (min-max)						
			kW	kW	kW	kW					
2 Room	7	7	2.00	2.00	4.00 (1.4-4.4)	1.09 (0.35-1.40)	3.67	4.0	6.7	A++	
	7	9	1.95	2.05	4.00 (1.4-4.4)	1.09 (0.35-1.40)	3.67	4.0	6.6	A++	
	7	12	1.65	2.35	4.00 (1.4-4.6)	1.05 (0.35-1.47)	3.81	4.0	6.5	A++	
	9	9	2.00	2.00	4.00 (1.4-4.5)	1.09 (0.35-1.43)	3.67	4.0	6.6	A++	
	9	12	1.70	2.30	4.00 (1.4-4.7)	1.05 (0.35-1.47)	3.81	4.0	6.5	A++	

- Note:
- 7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h models
 - The above is the value for connecting with Wall Mounted type.
 - 2 or more indoor units should be connected.
 - Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
 - Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
 - The Total ability of connected indoor unit is up to 21000Btu from 14000Btu.

AOYG18LAC2	Combination of Indoor Unit		COOLING OPERATION					EER	Seasonal Data		
			Cooling Capacity			Input Power (min-max)	Pdesign		SEER	Energy efficiency class	
			Room 1	Room 2	Total Capacity (min-max)						
			kW	kW	kW	kW					
2 Room	7	7	2.10	2.10	4.20 (1.7-5.2)	1.24 (0.35-1.68)	3.39	4.2	7.0	A++	
	7	9	2.10	2.50	4.60 (1.7-5.3)	1.26 (0.35-1.79)	3.65	4.6	6.8	A++	
	7	12	1.90	3.10	5.00 (1.7-5.6)	1.35 (0.35-1.95)	3.23	5.0	6.5	A++	
	7	14	1.80	3.20	5.00 (1.8-5.7)	1.55 (0.40-1.99)	3.23	5.0	6.5	A++	
	9	9	2.50	2.50	5.00 (1.7-5.6)	1.56 (0.35-1.95)	3.21	5.0	6.6	A++	
	9	12	2.10	2.90	5.00 (1.7-5.7)	1.55 (0.35-1.95)	3.23	5.0	6.5	A++	
	9	14	2.00	3.00	5.00 (1.8-5.8)	1.55 (0.40-1.99)	3.23	5.0	6.4	A++	
12	12	2.50	2.50	5.00 (1.7-5.8)	1.56 (0.35-1.99)	3.21	5.0	6.4	A++		


- Note:
- 7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h models
 - The above is the value for connecting with Wall Mounted type.
 - 2 or more indoor units should be connected.
 - Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
 - Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
 - The Total ability of connected indoor unit is up to 24000Btu from 14000Btu.
 - Where "14" means "wall mounted type" only models. Other types of indoor units can not be connected.

3 Rooms Multi cooling

AOYG18LAT3	Combination of Indoor Unit			COOLING OPERATION					EER	Seasonal Data		
				Cooling Capacity				Input Power (min-max)		Pdesign	SEER	Energy efficiency class
				Room 1	Room 2	Room 3	Total Capacity (min-max)					
				kW	kW	kW	kW					
2 Room	7	7	-	2.30	2.30	-	4.60 (1.8-5.0)	1.22 (0.50-1.43)	3.77	4.6	6.3	A++
	7	9	-	2.30	2.70	-	5.00 (1.8-5.7)	1.35 (0.50-1.81)	3.70	5.0	6.2	A++
	7	12	-	1.98	3.02	-	5.00 (1.8-6.1)	1.34 (0.50-2.06)	3.73	5.0	6.2	A++
	7	14	-	1.88	3.42	-	5.30 (1.8-6.6)	1.34 (0.50-2.06)	3.96	5.3	6.1	A++
	9	9	-	2.50	2.50	-	5.00 (1.8-6.2)	1.35 (0.50-2.06)	3.70	5.0	6.2	A++
	9	12	-	2.18	2.82	-	5.00 (1.8-6.3)	1.35 (0.50-2.06)	3.70	5.0	6.2	A++
	9	14	-	2.07	3.23	-	5.30 (1.8-6.7)	1.35 (0.50-2.06)	3.93	5.3	6.1	A++
	12	12	-	2.55	2.55	-	5.10 (1.8-6.3)	1.35 (0.50-2.06)	3.78	5.1	6.1	A++
	12	14	-	2.41	2.89	-	5.30 (1.8-6.7)	1.35 (0.50-2.06)	3.93	5.3	6.1	A++
	7	7	7	1.80	1.80	1.80	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.9	A++
3 Room	7	7	9	1.70	1.70	2.00	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.9	A++
	7	7	12	1.53	1.53	2.33	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.7	A++
	7	7	14	1.41	1.41	2.58	5.40 (2.0-6.8)	1.35 (0.60-2.06)	4.00	5.4	6.7	A++
	7	9	9	1.61	1.89	1.89	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.8	A++
	7	9	12	1.46	1.72	2.22	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.7	A++
	7	9	14	1.35	1.58	2.47	5.40 (2.0-6.8)	1.35 (0.60-2.06)	4.00	5.4	6.7	A++
	9	9	9	1.80	1.80	1.80	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.8	A++
	9	9	12	1.64	1.64	2.12	5.40 (1.8-6.8)	1.35 (0.50-2.06)	4.00	5.4	6.7	A++

AOYG24LAT3	Combination of Indoor Unit			COOLING OPERATION					EER	Seasonal Data		
				Cooling Capacity				Input Power (min-max)		Pdesign	SEER	Energy efficiency class
				Room 1	Room 2	Room 3	Total Capacity (min-max)					
				kW	kW	kW	kW					
2 Room	7	7	-	2.30	2.30	-	4.60 (1.8-5.0)	1.20 (0.50-1.40)	3.83	4.6	6.3	A++
	7	9	-	2.30	2.70	-	5.00 (1.8-5.7)	1.36 (0.50-1.78)	3.68	5.0	6.2	A++
	7	12	-	2.38	3.42	-	5.80 (1.8-6.1)	1.70 (0.50-1.97)	3.41	5.8	6.1	A++
	7	14	-	2.37	4.13	-	6.50 (1.8-7.2)	1.91 (0.50-2.46)	3.40	6.5	6.0	A+
	7	18	-	2.08	4.52	-	6.60 (1.8-7.8)	1.91 (0.50-2.87)	3.46	6.6	5.9	A+
	9	9	-	2.75	2.75	-	5.50 (1.8-6.2)	1.55 (0.50-2.02)	3.55	5.5	6.1	A++
	9	12	-	2.79	3.41	-	6.20 (1.8-6.8)	1.90 (0.50-2.45)	3.26	6.2	5.9	A+
	9	14	-	2.66	3.94	-	6.60 (1.8-7.7)	1.91 (0.50-2.77)	3.46	6.6	6.0	A+
	9	18	-	2.35	4.35	-	6.70 (1.8-7.9)	1.91 (0.50-2.87)	3.51	6.7	5.9	A+
	12	12	-	3.15	3.15	-	6.30 (1.8-7.2)	1.90 (0.50-2.74)	3.32	6.3	5.9	A+
	12	14	-	3.03	3.67	-	6.70 (1.8-7.8)	1.91 (0.50-2.87)	3.51	6.7	5.9	A+
	12	18	-	2.66	4.04	-	6.70 (1.8-7.9)	1.92 (0.50-2.87)	3.49	6.7	5.8	A+
	7	7	7	2.23	2.23	2.23	6.70 (1.8-7.4)	1.89 (0.50-2.37)	3.54	6.7	6.4	A++
	7	7	9	2.14	2.14	2.52	6.80 (1.8-7.8)	1.94 (0.60-2.87)	3.51	6.8	6.4	A++
	7	7	12	1.98	1.98	2.84	6.80 (1.8-8.1)	1.93 (0.50-2.87)	3.52	6.8	6.3	A++
	7	7	14	1.82	1.82	3.16	6.80 (2.0-8.4)	1.94 (0.60-2.87)	3.51	6.8	6.2	A++
	7	7	18	1.63	1.63	3.54	6.80 (2.0-8.5)	1.94 (0.60-2.87)	3.51	6.8	6.1	A++
	7	9	9	2.03	2.38	2.38	6.80 (1.8-8.2)	1.93 (0.50-2.87)	3.52	6.8	6.4	A++
	7	9	12	1.88	2.21	2.70	6.80 (1.8-8.2)	1.93 (0.50-2.87)	3.52	6.8	6.2	A++
	7	9	14	1.74	2.04	3.02	6.80 (2.0-8.4)	1.94 (0.60-2.87)	3.51	6.8	6.2	A++
	7	9	18	1.56	1.84	3.40	6.80 (2.0-8.5)	1.94 (0.60-2.87)	3.51	6.8	6.1	A++
3 Room	7	12	12	1.76	2.52	2.52	6.80 (1.8-8.2)	1.94 (0.50-2.87)	3.51	6.8	6.2	A++
	7	12	14	1.63	2.34	2.83	6.80 (2.0-8.5)	1.94 (0.60-2.87)	3.51	6.8	6.2	A++
	9	9	9	2.27	2.27	2.27	6.80 (1.8-8.2)	1.94 (0.50-2.87)	3.51	6.8	6.4	A++
	9	9	12	2.11	2.11	2.58	6.80 (1.8-8.3)	1.94 (0.50-2.87)	3.51	6.8	6.2	A++
	9	9	14	1.95	1.95	2.89	6.80 (2.0-8.5)	1.94 (0.60-2.87)	3.51	6.8	6.2	A++
	9	9	18 ^{*)}	1.77	1.77	3.27	6.80 (2.0-8.5)	1.94 (0.60-2.87)	3.51	6.8	6.1	A++
	9	12	12	1.97	2.41	2.41	6.80 (1.8-8.3)	1.94 (0.50-2.87)	3.51	6.8	6.2	A++
	9	12	14	1.84	2.24	2.72	6.80 (2.0-8.5)	1.94 (0.60-2.87)	3.51	6.8	6.2	A++
	12	12	12	2.27	2.27	2.27	6.80 (1.8-8.3)	1.94 (0.50-2.87)	3.51	6.8	6.1	A++

- Note:
- 7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h / 18:18000Btu/h models
 - The above is the value for connecting with Wall Mounted type.
 - 2 or more indoor units should be connected.
 - Cooling capacity is based on 27°CDB/19°CWB (indoor temperature), 35°CDB (outdoor temperature).
 - Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
 - The total ability of connectable indoor units is up to 36000Btu from 14000Btu.
 - *1: When ASYG18L is connected, connect at least 1 wall mounted type of 9000Btu.



2 Rooms Multi heating

AOYG14LAC2	Combination of Indoor Unit		HEATING OPERATION					Seasonal Data		
			Heating Capacity			Input Power (min-max)	EER	Pdesign	SEER	Energy efficiency class
			Room 1	Room 2	Total Capacity (min-max)					
			kW	kW	kW	kW				
2 Room	7	7	2.20	2.20	4.40 (1.1-5.4)	1.03 (0.25-1.78)	4.27	3.8	4.1	A+
	7	9	2.15	2.25	4.40 (1.1-5.4)	1.03 (0.25-1.78)	4.27	3.8	4.1	A+
	7	12	1.95	2.45	4.40 (1.1-5.5)	1.02 (0.25-1.76)	4.31	3.8	4.0	A+
	9	9	2.20	2.20	4.40 (1.1-5.4)	1.03 (0.25-1.78)	4.27	3.8	4.0	A+
	9	12	2.00	2.40	4.40 (1.1-5.5)	1.02 (0.25-1.76)	4.31	3.8	4.0	A+

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h models
 •The above is the value for connecting with Wall Mounted type.
 •2 or more indoor units should be connected.
 •Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
 •The Total ability of connected indoor unit is up to 21000Btu from 14000Btu.

AOYG18LAC2	Combination of Indoor Unit		HEATING OPERATION					Seasonal Data		
			Heating Capacity			Input Power (min-max)	EER	Pdesign	SEER	Energy efficiency class
			Room 1	Room 2	Total Capacity (min-max)					
			kW	kW	kW	kW				
2 Room	7	7	2.70	2.70	5.40 (1.8-6.0)	1.24 (0.50-1.61)	4.37	3.8	4.1	A+
	7	9	2.50	3.00	5.50 (1.8-6.0)	1.36 (0.50-1.87)	4.04	4.0	4.1	A+
	7	12	2.30	3.30	5.60 (1.8-6.1)	1.38 (0.50-1.88)	4.06	4.2	4.0	A+
	7	14	2.25	3.35	5.60 (1.9-6.2)	1.35 (0.55-1.86)	4.15	4.2	4.0	A+
	9	9	2.80	2.80	5.60 (1.8-6.1)	1.41 (0.50-1.90)	3.97	4.2	4.1	A+
	9	12	2.45	3.15	5.60 (1.8-6.2)	1.38 (0.50-1.88)	4.07	4.2	4.0	A+
	9	14	2.35	3.25	5.60 (1.9-6.3)	1.35 (0.55-1.86)	4.15	4.2	4.0	A+
12	12	2.80	2.80	5.60 (1.8-6.3)	1.34 (0.50-1.84)	4.18	4.2	4.0	A+	

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h models
 •The above is the value for connecting with Wall Mounted type.
 •2 or more indoor units should be connected.
 •Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
 •The Total ability of connected indoor unit is up to 24000Btu from 14000Btu.
 •Where "14" means "wall mounted type" only models. Other types of indoor units can not be connected.

3 Rooms Multi heating

AOYG18LAT3	Combination of Indoor Unit			HEATING OPERATION					Seasonal Data			
				Heating Capacity			Input Power (min-max)	EER	Pdesign	SEER	Energy efficiency class	
				Room 1	Room 2	Room 3						Total Capacity (min-max)
			kW	kW	kW	kW						
2 Room	7	7	-	2.70	2.70	-	5.40 (2.0-6.1)	1.59 (0.52-1.93)	3.40	4.0	4.1	A+
	7	9	-	2.75	3.25	-	6.00 (2.0-6.4)	1.87 (0.52-2.06)	3.21	4.0	4.1	A+
	7	12	-	2.59	3.71	-	6.30 (2.0-6.5)	1.98 (0.52-2.06)	3.18	4.0	4.1	A+
	7	14	-	2.51	4.29	-	6.80 (2.0-7.1)	1.92 (0.50-2.06)	3.54	4.0	4.1	A+
	9	9	-	3.15	3.15	-	6.30 (2.0-6.5)	1.98 (0.52-2.06)	3.18	4.0	4.1	A+
	9	12	-	2.89	3.51	-	6.40 (2.0-6.6)	1.99 (0.52-2.06)	3.22	4.0	4.1	A+
	9	14	-	2.77	4.03	-	6.80 (2.0-7.2)	1.91 (0.50-2.06)	3.56	4.0	4.1	A+
	12	12	-	3.20	3.20	-	6.40 (2.0-6.6)	1.98 (0.52-2.06)	3.23	4.0	4.1	A+
3 Room	12	14	-	3.09	3.71	-	6.80 (2.0-7.3)	1.90 (0.50-2.06)	3.58	4.0	4.1	A+
	7	7	7	2.27	2.27	2.27	6.80 (2.0-7.7)	1.62 (0.50-2.06)	4.20	5.0	4.3	A+
	7	7	9	2.14	2.14	2.52	6.80 (2.0-7.8)	1.62 (0.50-2.06)	4.20	5.0	4.3	A+
	7	7	12	1.98	1.98	2.93	6.80 (2.0-7.8)	1.59 (0.50-2.06)	4.28	5.0	4.3	A+
	7	7	14	1.83	1.83	3.14	6.80 (2.0-8.0)	1.61 (0.50-2.06)	4.22	5.0	4.3	A+
	7	9	9	2.03	2.39	2.39	6.80 (2.0-7.8)	1.60 (0.50-2.06)	4.25	5.0	4.3	A+
	7	9	12	1.89	2.22	2.69	6.80 (2.0-7.9)	1.59 (0.50-2.06)	4.28	5.0	4.3	A+
	7	9	14	1.75	2.06	2.99	6.80 (2.0-8.0)	1.60 (0.50-2.06)	4.25	5.0	4.3	A+
	9	9	9	2.27	2.27	2.27	6.80 (2.0-7.9)	1.59 (0.50-2.06)	4.28	5.0	4.3	A+
	9	9	12	2.12	2.12	2.57	6.80 (2.0-7.9)	1.59 (0.50-2.06)	4.28	5.0	4.3	A+

AOYG24LAT3	Combination of Indoor Unit			HEATING OPERATION					Seasonal Data			
				Heating Capacity			Input Power (min-max)	EER	Pdesign	SEER	Energy efficiency class	
				Room 1	Room 2	Room 3						Total Capacity (min-max)
			kW	kW	kW	kW						
2 Room	7	7	-	2.75	2.75	-	5.50 (2.0-6.1)	1.55 (0.52-1.93)	3.55	4.0	4.1	A+
	7	9	-	2.80	3.30	-	6.10 (2.0-7.0)	1.82 (0.52-2.52)	3.35	4.0	4.1	A+
	7	12	-	2.88	4.12	-	7.00 (2.0-7.3)	2.31 (0.52-2.66)	3.03	4.0	4.1	A+
	7	14	-	2.80	4.80	-	7.60 (2.0-8.3)	2.28 (0.50-2.87)	3.33	4.0	4.1	A+
	7	18	-	2.51	5.39	-	7.90 (2.0-8.3)	2.34 (0.50-2.87)	3.38	4.0	4.1	A+
	9	9	-	3.30	3.30	-	6.60 (2.0-7.4)	2.04 (0.52-2.68)	3.24	4.0	4.1	A+
	9	12	-	3.30	4.00	-	7.30 (2.0-7.7)	2.43 (0.52-2.87)	3.00	4.0	4.1	A+
	9	14	-	3.22	4.68	-	7.90 (2.0-8.3)	2.38 (0.50-2.87)	3.32	4.0	4.1	A+
	9	18	-	2.84	5.16	-	8.00 (2.0-8.5)	2.32 (0.50-2.87)	3.45	4.0	4.1	A+
	12	12	-	3.80	3.80	-	7.60 (2.0-7.8)	2.54 (0.52-2.87)	2.99	4.0	4.1	A+
	12	14	-	3.59	4.31	-	7.90 (2.0-8.4)	2.37 (0.50-2.87)	3.33	4.0	4.1	A+
	12	18	-	3.20	4.80	-	8.00 (2.0-8.6)	2.31 (0.50-2.87)	3.46	4.0	4.1	A+
	7	7	7	2.60	2.60	2.60	7.80 (2.0-8.6)	1.94 (0.50-2.68)	4.02	5.0	4.3	A+
	7	7	9	2.52	2.52	2.96	8.00 (2.0-8.8)	2.00 (0.50-2.87)	4.00	5.2	4.2	A+
	3 Room	7	7	12	2.34	2.34	3.32	8.00 (2.0-8.9)	1.99 (0.50-2.80)	4.02	5.2	4.2
7		7	14	2.16	2.16	3.68	8.00 (2.0-9.2)	1.91 (0.50-2.72)	4.19	5.2	4.2	A+
7		7	18	1.94	1.94	4.12	8.00 (2.0-9.2)	1.89 (0.50-2.70)	4.23	5.2	4.2	A+
7		9	9	2.38	2.81	2.81	8.00 (2.0-9.0)	1.99 (0.50-2.87)	4.02	5.2	4.2	A+
7		9	12	2.23	2.62	3.15	8.00 (2.0-9.1)	1.98 (0.50-2.87)	4.04	5.2	4.2	A+
7		9	14	2.06	2.42	3.52	8.00 (2.0-9.2)	1.91 (0.50-2.72)	4.19	5.2	4.2	A+
7		9	18	1.85	2.18	3.97	8.00 (2.0-9.2)	1.89 (0.50-2.69)	4.23	5.2	4.2	A+
7		12	12	2.08	2.96	2.96	8.00 (2.0-9.1)	1.97 (0.50-2.87)	4.06	5.2	4.2	A+
7		12	14	1.93	2.76	3.31	8.00 (2.0-9.2)	1.90 (0.50-2.70)	4.21	5.2	4.2	A+
9		9	9	2.67	2.67	2.67	8.00 (2.0-9.1)	1.98 (0.50-2.87)	4.04	5.2	4.2	A+
9		9	12	2.49	2.49	3.02	8.00 (2.0-9.2)	1.97 (0.50-2.87)	4.06	5.2	4.2	A+
9		9	14	2.32	2.32	3.37	8.00 (2.0-9.2)	1.89 (0.50-2.70)	4.23	5.2	4.2	A+
9		9	18*	2.10	2.10	3.81	8.00 (2.0-9.2)	1.87 (0.50-2.68)	4.28	5.2	4.2	A+
9		12	12	2.34	2.83	2.83	8.00 (2.0-9.2)	1.96 (0.50-2.80)	4.08	5.2	4.2	A+
9		12	14	2.18	2.64	3.17	8.00 (2.0-9.2)	1.89 (0.50-2.69)	4.23	5.2	4.2	A+
12	12	12	2.67	2.67	2.67	8.00 (2.0-9.2)	1.95 (0.50-2.78)	4.10	5.2	4.2	A+	

Note: •7:7000Btu/h / 9:9000Btu/h / 12:12000Btu/h / 14:14000Btu/h / 18:18000Btu/h models
 •The above is the value for connecting with Wall Mounted type.
 •2 or more indoor units should be connected.
 •Heating capacity is based on 20°CDB (indoor temperature), 7°CDB/6°CWB (outdoor temperature).
 •Pipe Length: 5 m, Height difference: 0 m (Outdoor unit to Indoor unit)
 •The Total ability of connected indoor unit is up to 36000Btu from 14000Btu.
 *1: When ASYG18L is connected, connect at least 1 wall mounted type for 9000Btu.

